

DECLARATION OF PERFORMANCE



REFERENCE NUMBER: KU0044-07-1, KU0044-07-05-1,
KU0044-07-11-1

1. IDENTIFICATION CODE: **Underlay**
2. PRODUCT: **Permo® forte NG, Permo® forte NG SK²**
3. IDENTIFICATION OF CP: Underlays for discontinuous roofing
Underlays for walls
4. MANUFACTURER: **Klöber GmbH**
Scharpenberger Str. 72-90
58256 Ennepetal
Germany
6. SYSTEM: **System 3**
7. NOTIFIED BODY: FIW e.V. München, Lochhamer Schlag 4, 82166 Gräfeling,
Not. No.: 0751
respectively MPA, Beethovenstraße 52, 38106 Braunschweig,
Not. No.: 0761

9. DECLARED PERFORMANCE ACCORDING TO EN 12311-1 / EN 12311-1

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	E	EN 12311-1
Resistance to water penetration	W1	
Tensile strength (N/50mm) (long./transv.)	430 / 370 +/-30	
Resistance to tearing (N) (nail shank)	320 / 340 +/-30	
Pliability	-25°C	
Tensile Strength (N/50mm) after ageing (long./transv.)	380 / 320 +/-30	
Resistance to water penetrations after ageing	W1	

10. The declaration of performance is identified in points 1 and 2 is in conformity with the declared performance in table 9.
The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

David Arendell (Managing Director)

Andrew Brewin (Finance Director)