




CE Marking information for slate for discontinuous roofing and cladding, AVCP System 4

Description of product

Sierra Roofing Slate – nominal thickness (4.2mm)

			
Lagan Building Solutions Ltd, 11B Sheepwalk Road, Lisburn. Co Antrim. BT28 3RD.			
EN12326-1:2014			
Sierra Roofing Slate			
Intended to be used as discontinuous roofing and external cladding			
Nominal Thickness	Available as 4.2mm		
Individual Thickness	4.2mm (< ± 35%)		
Deviation of length and width, edge straightness and squareness	Complies		
Mechanical Resistance (Characteristic MoR)	Transverse	58 MPa	Longitudinal 60 MPa
Water Permeability – water absorption	W1 ≤ 0.6%		
Apparent calcium carbonate	< 5%		
Durability:			
Water absorption	W1 ≤ 0.6%		
Freeze thaw cycling	Not required		
Thermal cycling	T1		
Sulphur dioxide exposure	S1		
Non-carbonate carbon	Complies: ≤ 2%		
Release of dangerous substances	None in conditions as roofing or external cladding		
External fire performance	Deemed to satisfy		
Reaction to fire	Deemed to satisfy class A1		

Dangerous Substances

All LBS slate roofing products are inert unless the physical characteristics of the individual items are altered by processing. In conditions of use as roofing or external cladding, this product does not release dangerous substances.

The performance of the product identified above is in conformity with the declared performance in the above table. This declaration of performance is issued under the sole responsibility of Lagan Building Solutions Ltd.

Signed for and on behalf of LBS by:



LBS, 11b Sheepwalk Road, Lisburn. BT28 3RD. Tel: 02892648691

E: info@LBSproducts.com W: www.LBSproducts.com