



Deep / Preparation Cleaning Of Porous Building Material

1. External Natural Stone and concrete paving also suitable for garden walls and timber decking = **Stontex All In One Outdoor Cleaner 5L**, coverage rate depends on how dirty the material is but average 5L = 30sqm. Do Not Spray, mix in bucket 1 to 1 and apply with a deck brush agitate well and solution will foam up like shampoo allow to dwell for up to 30mins then power wash / hose the area with water.
2. External Natural Stone, Brick, Roof Tiles, Render and Wooden cladded walls = **Stontex Green To Clean 5L**, coverage rate depends on how dirty the material is but average 5L = 80sqm. Spray the diluted 1 to 5 mix, onto the stained surface and allow to dwell overnight then power wash / hose the area with water.
3. Internal Natural Stone, ceramic and porcelain internal floor tiles = **Stontex Heavy Duty Grime Remover 1L**, coverage rate depends on how dirty the material is but average 1L = 50sqm, dilute 1 to 10 and apply by agitating surface with a nylon brush allow to dwell for 15mins and wash thoroughly with clean water.

Protection Of Porous Building Material

1. Natural Stone paving / tiles with natural look finish = **Stontex Rapid Dry Stone Sealer 1L & 5L**, coverage rate 8sqm to 12sqm depending on porosity of the material, normally 1 coat treatment but additional coat may be required for added protection.
2. Natural Stone paving / tiles with wet look finish = **Stontex Colour Intensifier 1L & 5L** coverage rate 8sqm to 12sqm depending on porosity of the material, normally 1 coat treatment but additional coat may be required to uniform the colour.
3. Natural Stone, Brick, Render, cladded walls also Roof Tiles to achieve a natural look finish = **Stontex Façade Pro500 25L**, coverage rate 4sqm to 8sqm depending on porosity of the material, normally 1 coat treatment but additional coat may be required for added protection.
4. Mono Block / Concrete Block paving driveways natural look finish (additional coats will give a wet look) = **Stontex Paver Plus 5L & 25L**, coverage rate 3sqm to 6sqm depending on size of the blocks, normally 1 coat treatment but additional coats may be required to enhance the colour. Consolidates the kiln dried sand in the joints and seals the face of the paver for stain protection.



Ongoing Maintenance Of Porous Building Material

- 1 External Natural Stone and concrete paving also suitable for garden walls and timber decking = **Stontex Green to Clean 5L**, coverage rate depends on how dirty the material is but average 5L = 100sqm. Spray directly onto the algae/ lichen stained surface, mix in a 25L knapsack sprayer 1x 5L green to clean and fill rest of container with water this is a full-strength mix. Pick a dry day as needs to be dry at least four hours after application, then simply spray and walk away within a few days up to two weeks all organic stains will be gone and active enzymes will continue to work for up to 9 months. No power washing or scrubbing of any kind cleaner activated by UV new innovative technology.
- 2 External Natural Stone, Brick, Roof Tiles, Render and Wooden cladded walls = **Stontex Green To Clean 5L**, coverage rate depends on how dirty the material is but average 5L = 100sqm. Spray directly onto the algae/ lichen stained surface, mix in a 25L knapsack sprayer 1x 5L green to clean and fill rest of container with water this is a full-strength mix. Pick a dry day as needs to be dry at least four hours after application, then simply spray and walk away within a few days up to two weeks all organic stains will be gone and active enzymes will continue to work for up to 9 months. No power washing or scrubbing of any kind cleaner activated by UV new innovative technology
- 3 Internal Natural Stone, ceramic and porcelain floor tiles = **Stontex Multi Clean 1L**, coverage rate average 1L = 800sqm, dilute 1 to 50 and apply by mop and bucket however a steam mop would be much better that way you are not moving the dirty water all around the floor. Our **Stontex Multi Clean 1L** is also a disinfectant kills e-coli, MRSA and other common bacteria and has a unique streak free formula for polished floor tiles.